

Singer Linear Inductive Valve Position Transmitter Model X156

SINGER®
a **MUELLER** brand

Technical Guide W4.70

The X156 Linear Inductive Valve Position Transmitter electronically indicates the position of the valve and is ideal for applications where precision and accuracy is required.



10.25 | W4.70 SINGER LINEAR INDUCTIVE VALVE POSITION TRANSMITTER MODEL X156

Applications

Pressure Control

Potable water

Municipal

Mining Applications

Irrigation Applications

Product Attributes

The stainless-steel actuator stem is pinned directly to the main valve stem

Stems on Main Valves larger than 65 mm are pre-drilled for easy installation

Separate stem cap permits easy field installation

Approvals/Standards

Combination water-tight rated enclosure to NEMA 4X and NEMA 6



Licence Number:
WMK/SMK26726

We are the supply partner of choice for New Zealand's civil construction industry, specialising in water and infrastructure based solutions.

HYNDSwater

The X156 Linear Inductive Valve Position Transmitter is mounted directly to the main valve stem and uses an external source of 24 VDC power, a 4 to 20 mA signal proportional to valve stroke is generated and transmitted. The zero and span are fully adjustable over the complete range of stroke.

STANDARD MATERIALS

- Adapter: ASTM B-16
- Target: AISI 416 stainless-steel
- Actuator Stem: AISI 316 stainless-steel
- O-Ring Seals: Buna-N
- Seal Bushing: ASTM B-16 brass
- Mounting Plate: Coated steel
- Actuator Stem Pin: 18-8 stainless-steel

ORDERING INSTRUCTIONS

- Available without 4-20 mA rescaler
 - Available with optional external limit switches
- Refer to the order form and ordering instructions. Additionally, include the following information for this product:
- Integrated discrete switch output (optional)

SIZES AND HEIGHTS



TABLE 1 Singer Linear Inductive Valve Position Transmitter Model X156

Size (mm)	106-X156 (mm)	206-X156 (mm)
65	230	230
80	230	230
100	230	230
150	230	230
200	230	230
250	230	230
300	230	230
350	230	-
400	230	230
450	-	230
500	318	230
600	318	230
600 x 400	-	230
600 x 500	-	230
700	-	318
750	-	318
800	-	318
900	-	318
1000	788	318
1200	-	318

Note: Dimension G in the above image is the height added to the valve by the assembly.

Branches Nationwide Support Office & Technical Services 0800 93 7473

Disclaimer: While every effort has been made to ensure that the information in this document is correct and accurate, users of Hynds product or information within this document must make their own assessment of suitability for their particular application. Product dimensions are nominal only, and should be verified if critical to a particular installation. No warranty is either expressed, implied, or statutory made by Hynds unless expressly stated in any sale and purchase agreement entered into between Hynds and the user.